



In-Ceiling/In-Wall Loudspeakers

APPLICATIONS

- Corporate and residential buildings
- Commercial premises
- Leisure centres
- Health and sports centres
- Meeting and conference rooms
- Auditoriums, museums

eIC52MS:

- Saunas, spas, ships, harbors, etc.

eIC51 / eIC52 / eIC5154 / eIC52MS is a cost-effective in-ceiling installation loudspeaker with a great sound performance.



eIC51



eIC52MS



eIC52



eIC5154

KEY FEATURES

- ABS speaker
- Built-in audio transformer for 70/100 V use
- Clip-type input terminals and low impedance / high impedance power tap selector
- EN54-24 Certified (eIC5154)
- Suitable for installations exposed to extreme humidity and/or temperature (eIC52MS)

	eIC51	eIC52	eIC5154	eIC52MS
RMS power / Program power (8Ω)	10W / 20W	20W / 40W	-	20 / 35W
Woofer / tweeter	5,25" / -	5,25" / 0,75"	5" / -	5" / 1"
Power selector @ 100V	3/6 W	3/6 W	0,38/0,75/1,5/3/6 W	-
SPL 1W/1m	88 dB	86 dB	92 dB	TBC
Dimensions / Weight	IntxExtxD (mm): 164x202x60 / 0,9 kg.	IntxExtxD (mm): 164x202x65 / 1,0 kg.	IntxExtxD (mm): 158x180x147 / 1,2 kg.	IntxExtxD (mm): 120x165x60 / 0,6 kg.